

MULTI-PURPOSE CYLINDERS CILINDRI PER USO INDUSTRIALE

CMI

Force / Forza: 5 - 100 t

Stroke / Corsa: 25 - 350 mm

Max. working pressure / Pressione max. di servizio: 700 bar



**SPRING RETURN
RITORNO A MOLLA**

Pushing force	Stroke	Oil volume	MODEL	Closed height	External Dia.	Weight
t* kN	mm	cm ³		A mm	D mm	kg
5 49,5	25	18	CMI5N25	92	40	1,1
	50	35	CMI5N50	117		1,3
	75	53	CMI5N75	142		1,5
	125	88	CMI5N125	202		1,9
	175	124	CMI5N175	252		2,3
	225	159	CMI5N225	302		2,7
10 111	25	40	CMI10N25	83	60	2,0
	50	80	CMI10N50	120		2,6
	100	159	CMI10N100	170		3,5
	150	238	CMI10N150	245		4,7
	200	318	CMI10N200	295		5,6
	250	398	CMI10N250	345		6,5
	300	477	CMI10N300	408		9,03
	350	557	CMI10N350	458		10
25 232	25	83	CMI25N25	119	85	4,6
	50	166	CMI25N50	144		5,3
	100	332	CMI25N100	214		7,5
	150	498	CMI25N150	264		8,8
	200	664	CMI25N200	314		10,2
	250	830	CMI25N250	364		11,6
	300	996	CMI25N300	414		13,0
	350	1161	CMI25N350	464		15,0
30 309	210	928	CMI30N210	386	102	18,4
50 496	50	354	CMI50N50	164	127	14,2
	100	709	CMI50N100	214		17,4
	150	1063	CMI50N150	264		20,8
	325	2304	CMI50N325	439		32,6
100 929	100	1327	CMI100N100	246	175	39,6
	150	1991	CMI100N150	296		46,0