

# DOUBLE ACTING INDUSTRIAL CYLINDERS CILINDRI PER SPINTA E TRAZIONE

## COD

Force / Forza: 5 - 25 t

Stroke / Corsa: 30 - 260 mm

Max. working pressure / Pressione max. di servizio: 700 bar

**OIL RETURN  
RITORNO AD OLIO**



Pushing force	Pulling force	Stroke	Pushing oil volume	Pulling oil volume	MODEL	Closed height	External Dia.	Weight
						A mm	D mm	kg
<b>5</b> 49,5	<b>3</b> 27,5	30	21	12	<b>COD5N30</b>	185	50	2,1
		80	57	31	<b>COD5N80</b>	235		2,8
		160	113	63	<b>COD5N160</b>	315		3,8
<b>10</b> 97	<b>6</b> 62	30	42	27	<b>COD10N30</b>	204	63	3,6
		80	111	72	<b>COD10N80</b>	254		4,5
		160	222	143	<b>COD10N160</b>	334		5,8
<b>15</b> 137	<b>8</b> 81	260	360	233	<b>COD10N260</b>	434	80	7,3
		160	314	185	<b>COD15N160</b>	376		10,8
<b>25</b> 232	<b>12</b> 121	260	511	301	<b>COD15N260</b>	476	92	13,9
		160	531	276	<b>COD25N160</b>	412		15,5
		260	863	449	<b>COD25N260</b>	512		19,4