



Hydraulic Tensioner Pump

The air-operated 10-6 series pump is a safe, low maintenance and durable unit that meets the requirements of all on-site bolt tensioning operational needs.

This air operated pump is particularly suitable for projects where a higher oil flow is required, such as subsea duties or where a large number of high capacity tensioners are being used.

Physical Description

Width:	14.96"	380 mm
Height:	17.24"	438 mm
Depth:	15.75"	400 mm
Weight (without fluid):	52 lbs	23.5 kg

Air Consumption

1.586 m³ per minute
 1586 litres per minute
 56 cubic feet per minute

D3001A0115AA (Approximate Rate of Discharge Litres per Minute/
 Cubic Inches per Minute)

Air		Fluid Discharge Pressure (bar/psi)															
bar	psi	0	0	207	3000	414	6000	621	9000	862	12500	1034	15000	1379	20000	1724	25000
4	60	1.00	61	0.80	49	0.70	43	0.62	38	0.51	31	0.44	27	0.00	0.0	0.00	0.0
6	80	1.07	65	0.93	57	0.84	51	0.75	46	0.66	40	0.61	37	0.49	30	0.16	10
7	100	1.15	70	0.97	59	0.88	54	0.80	49	0.72	44	0.66	40	0.56	34	0.46	28

