


CV-I EXPLOSION VENTS

DESCRIPTION

Fike designs simple, reliable explosion protection solutions to meet your safety requirements. The Fike CV-I vent is a composite membrane, high performance explosion vent that provides service life for static to light pressure cycling conditions. The CV-I vent is constructed with insulation to accommodate higher temperature processes, up to 800°F / 425°C.

Typical applications include separation, drying, storage, conveyance, and processing operations.



STANDARD FEATURES AND BENEFITS

Instantaneous Full Opening	Reduced risk for accidental contamination, elimination of undetected openings
Fail-Safe Design	Certified burst pressure provides full, predictable opening at or below its rated burst pressure even if the vent is damaged
Dynamically Tested - Fike exclusive!	Tested under full-scale explosion conditions not just computer modeling
100% Venting Efficiency	Optimal relief area
High Mechanical Integrity	Longer service life
Easy Installation by Plant Personnel	Reduced downtime and maintenance costs
Non-Fragmenting Design	Reduced risk to personnel and equipment
Maintenance Free	Reduced cost of ownership

SPECIFICATIONS

Compliance:	NFPA 68
Materials of Construction:	316 SST / FEP or PFA / Fiberfrax insulation / 316 SST
Maximum Operating Pressure/Vacuum Rating:	75% of the minimum stamped burst pressure for BP ≤ 1.5 psig 60% of the minimum stamped burst pressure for BP > 1.5 psig
Standard Burst Pressure Tolerance:	± 0.25 psig for burst pressures < 1.0 psig ± 0.5 psig for burst pressures 1.0 - 4.0 psig ± 1.0 psig for burst pressures > 4.0 psig
Operating Temperature Range:	-40°C up to 425°C / -40°F up to 800°F
Optional Equipment:	Burst Indicators / Monitoring System; Alternative materials, temperature ranges, and tighter tolerances are available

Form No. X.1.17.01-4

Vent Size		Relief Area		Minimum Burst Pressure		Maximum Burst Pressure	
in	cm	ft ²	m ²	psig	mbarg	psig	mbarg
9 x 12	23 x 30	0.61	.057	2.0	138	10.0	690
12 x 12	30 x 30	0.84	.078	2.0	138	8.0	550
12 x 18	30 x 46	1.30	.12	1.5	103	8.0	550
12 x 24	30 x 61	1.76	.16	1.5	103	8.0	550
18 x 18	46 x 46	2.01	.19	1.0	69	8.0	550
18 x 24	46 x 61	2.72	.25	1.0	69	8.0	550
18 x 30	46 x 76	3.42	.32	1.0	69	8.0	550
24 x 24	61 x 61	3.67	.34	1.0	69	8.0	550
20 x 30	51 x 76	3.83	.36	1.0	69	8.0	550
18 x 35	46 x 89	4.01	.37	1.0	69	8.0	550
18 x 36	46 x 91	4.13	.38	1.0	69	8.0	550
24 x 30	61 x 76	4.63	.43	1.0	69	8.0	550
24 x 36	61 x 91	5.59	.52	.5	35	8.0	550
30 x 30	76 x 76	5.84	.54	.5	35	8.0	550
24 x 44	61 x 112	6.87	.64	.5	35	8.0	550
30 x 36	76 x 91	7.05	.66	.5	35	8.0	550
24 x 48	61 x 122	7.51	.70	.5	35	8.0	550
36 x 36	91 x 91	8.51	.79	.5	35	8.0	550
30 x 44	76 x 112	8.66	.81	.5	35	8.0	550
36 x 44	91 x 112	10.45	.97	.5	35	8.0	550
44 x 44	112 x 112	12.84	1.19	.5	35	8.0	550
44 x 69	142 x 175	20.31	1.89	.5	35	8.0	550
6 Dia	15 Dia	.14	.013	3.0	207	15.0	1030
8 Dia	20 Dia	.28	.026	2.5	172	15.0	1030
10 Dia.	25 Dia.,	.45	.042	2.0	138	11.0	760
12 Dia.	30 Dia.	.68	.063	2.0	138	10.0	690
14 Dia.	36 Dia.	.95	.088	1.5	103	10.0	690
16 Dia.	41 Dia.	1.27	.12	1.25	86	10.0	690
18 Dia.	46 Dia.	1.62	.15	1.0	69	10.0	690
20 Dia.	51 Dia.	2.02	.19	1.0	69	10.0	690
22 Dia.	56 Dia.	2.46	.23	1.0	69	10.0	690
24 Dia.	61 Dia.	2.95	.27	1.0	69	10.0	690
26 Dia.	66 Dia.	3.48	.32	.8	69	10.0	690
30 Dia.	76 Dia.	4.67	.43	.5	35	10.0	690
36 Dia.	91 Dia.	6.78	.63	.5	35	10.0	690
40 Dia.	102 Dia.	8.40	.78	.5	35	10.0	690
44 Dia.	112 Dia.	10.20	.95	.5	35	10.0	690

- Custom sizes are available
- All dimensions are nominal

INSTALLATION

CV-I rectangular and circular vents with standard designs are mounted in several lightweight angle frame configurations. CV circular explosion vents can also be installed between standard weld neck flanges in accordance with DIN 3632 PN10 or ANSI B16.5 150. Fike offers frames of multiple configurations and materials. If you prefer to make your own frames, drawings can be purchased for a nominal fee.

HOW TO ORDER

Previous Lot Number:	
OR	
Size:	
Burst Pressure:	@ (Temperature)
Top Material:	
Seal Material:	
Support Material:	
Frame Drawing or Bolt Pattern:	

