

TQ SERIES PRETORQUEABLE RUPTURE DISC HOLDERS

Fike offers two types of pretorqueable holders, the “TQ+” and “TQ”. The purpose of the TQ+ and TQ holder designs are to allow rupture discs to be installed and then “torqued” to recommended static load levels ensuring proper clamping of the rupture disc within the assembly. This can take place at a workbench rather than in the field where conditions could be less than ideal, greatly reducing the possibility of assembly errors.

Once together, the rupture disc assembly may then be delivered to the field location and installed between companion flanges where additional torque loads applied are essential for proper functionality of the assembly. TQ+ and TQ assemblies may also be removed, inspected and replaced during routine maintenance schedules and plant turnarounds without compromising disc performance as long as the disc is not removed.



TQ+ Holder



TQ Holder

TQ+ RUPTURE DISC HOLDERS

The TQ+ type holders were designed with the ability to be installed in multiple international flange rating configurations. The TQ+ can be specified for the following rupture disc models: Axis, SRL, SRX and Poly-SD.

DISC/HOLDER MODEL COMPATIBILITY

Disc Model	Holder Model			
	SRX	SRL	XL	Poly-SD
SRX	✓			
SRL		✓	✓ *	
Axis		✓ **	✓	
Poly-SD				✓

* 1.50” (DN40) SRL disc not compatible with 1.50” (DN40) XL Holder.

** 1.50” (DN40) Axis disc not compatible with 1.50” (DN40) SRL Holder.

FEATURES OF TQ+ RUPTURE DISC HOLDERS

- Suitable for ANSI, JIS, DIN, and ISO ratings. Ratings may vary by size.
- DiscLoc™ locator helps prevent inverted disc installation. Available on XL, SRL, and SRX models
- Serrated gasket faces per ANSI B16.5 for improved gasket sealing
- Standard stocked size range from 1 to 6 inch (DN25 – DN150).
- Standard 316 Stainless Steel material of construction. (Other materials available upon request)
- Standard overall height dimensions
- High profile or “tall” holddowns are available for XL and 1.50 inch (DN40) SRL models and are recommended when installed directly under relief valves.

Form No. R.1.45.01-2

TQ+ SERIES PRETORQUEABLE HOLDERS FOR AXIUS, SRL, SRX AND POLY-SD

Size (mm)	Assembly Height				Flange Rating	Max NPT Size Low Profile	Max NPT Size High Profile
	XLO	XL	SRX	Poly-SD			
1" (DN25)	1.50 (38.1)	2.38 (60.5)	1.50 (38.1)	1.50 (38.1)	ANSI 150-600, ISO PN10-PN100, DIN PN10-PN40, JIS 10K-20K	None	1/4"
1.50" (DN40)	1.69 (42.9)	2.88 (73.2)	1.69 (42.9)	1.69 (42.9)	ANSI 150-600, ISO PN10-PN100, DIN PN10-PN40, JIS 10K-20K	1/4"	1/4"
2" (DN50)	1.88 (47.8)	3.00 (76.2)	1.88 (47.8)	1.88 (47.8)	ANSI 150-600, ISO PN10-PN100, DIN PN10-PN64, JIS 10K-40K	1/4"	1/4"
3" (DN80)	2.14 (54.1)	3.75 (95.3)	2.14 (54.1)	2.14 (54.1)	ANSI 150-600, ISO PN10-PN100, DIN PN10-PN40, JIS 10K-20K	1/4"	1/4"
4" (DN100)	2.88 (73.1)	4.56 (115.8)	2.88 (73.1)	2.88 (73.1)	ANSI 150, ISO PN20-PN40, DIN PN25-PN64, JIS 16K-30K	1/4"	1/4"
4" (DN100)	2.88 (73.1)	4.56 (115.8)	2.88 (73.1)	2.88 (73.1)	ANSI 300-600 ISO PN50-PN100, JIS 40K-63K	1/4"	1/4"
6" (DN150)	3.69 (93.7)	6.00 (152.4)	3.69 (93.7)	3.69 (93.7)	ANSI 150, ISO PN16-PN40, DIN PN16-PN40, JIS 10K	1/2"	1/2"
6" (DN150)	3.69 (93.7)	6.00 (152.4)	3.69 (93.7)	3.69 (93.7)	ANSI 300, ISO PN50, JIS 30K	1/2"	1/2"

Notes:

- 1.50" SRL assembly height 1.69" (42.9mm); Max NPT 1/4"
- 1.50" SRL assembly height 2.88 (73.2mm); Max NPT 1/4"
- 4" Holddowns (all heights) are limited to 1/4 NPT.

TQ RUPTURE DISC HOLDERS

TQ type holders are manufactured to the specified flange rating and diameters corresponding to nominal pipe sizes. TQ holder standard materials of construction are carbon steel and 316 SST. Other materials and custom holder heights are available upon request. TQ holders can be specified for the following rupture disc models: Axius, SRL, SRX and Poly-SD.

DISC/HOLDER MODEL COMPATIBILITY

Disc Model	Holder Model			
	SRX	SRL	XL	Poly-SD
SRX	✓			
SRL		✓	✓*	
Axius		✓**	✓	
Poly-SD				✓

* 1.50" (DN40) SRL disc not compatible with 1.50" (DN40) XL Holder.

** 1.50" (DN40) Axius disc not compatible with 1.50" (DN40) SRL Holder.

FEATURES OF TQ RUPTURE DISC HOLDERS

- Standard sizes ranging from 1 to 12 inch (DN25-DN300)
- DiscLoc™ locator helps prevent inverted disc installation. Available on XL, SRL, and SRX models
- Serrated gasket faces per ANSI B16.5 for improved gasket sealing
- Optional O-Ring disc seal for reduced emissions on XL, SRL, and SRX models
- Standard 316 Stainless and Carbon Steel materials of construction. (Other materials available upon request)

TQ SERIES PRETORQUEABLE HOLDERS FOR AXIUS, SRL, SRX AND POLY-SD

Size	Assembly Height		Max. NPT Size (ANSI 150)	Assembly Height SRX	Max. NPT Size (ANSI 150)	Assembly Height ANSI 150	Assembly Height ANSI 300	Max. NPT Size (ANSI 150/300)
	XLO	XL				Poly-SD	Poly-SD	
1" (DN25)	2.25 (57.2)	2.63 (66.8)	1/2"	2.13 (54.1)	1/2"	1.50 (38.1)	1.50 (38.1)	1/4"
1.50" (DN40)	2.13 (54.1)	3.13 (79.5)	1/2"	2.25 (57.2)	1/4"	1.63 (41.4)	1.63 (41.4)	1/4"
2" (DN50)	2.63 (66.8)	3.44 (87.4)	1/4"	2.69 (68.3)	1/4"	1.75 (44.5)	1.75 (44.5)	1/4"
3" (DN80)	2.56 (65.0)	4.16 (105.7)	1/2"	2.63 (66.8)	1/2"	2.13 (54.1)	2.13 (54.1)	1/2"
4" (DN100)	2.75 (69.9)	4.75 (120.7)	1/2"	2.88 (73.2)	1/2"	2.88 (73.2)	2.88 (73.2)	1/2"
6" (DN150)	2.81 (71.4)	6.00 (152.4)	1/2"	2.94 (74.7)	1/2"	3.38 (85.9)	3.69 (93.7)	1/2"
8" (DN200)	3.06 (77.7)	7.56 (192.0)	1/2"	3.22 (81.8)	1/2"	3.50 (88.9)	3.75 (95.3)	1/2"
10" (DN250)	4.03 (102.4)	9.59 (243.6)	1/2"	3.94 (100.1)	1/2"	3.94 (100.1)	3.94 (100.1)	1/2"
12" (DN300)	4.91 (124.7)	11.53 (292.9)	1/2"	4.56 (115.8)	1/2"	3.94 (100.1)	5.19 (131.8)	1/2"

Notes:

- 1.50" SRL assembly height 2.13" (54.1mm); Max NPT 1/2"
- 1.50" SRL assembly height 2.63 (66.8mm); Max NPT 1/2"

For holder configurations other than the pretorqueable style (for example, insert, full-bolting, welded, or threaded versions) please consult factory.

CERTIFICATIONS



ASME Authorized
Specify When Ordering



Copyright © Fike Corporation All Rights Reserved.
Form No. R.1.45.01-2 November, 2010 Specifications are subject to change without notice.