

## SR-H RUPTURE DISC

### DESCRIPTION

The SR-H is a reverse acting, scored rupture disc for use in sanitary applications and carries the 3-A symbol. Fike's SR-H rupture disc incorporates the Contour Modified™ design giving the SR-H superior performance in extreme operating conditions. The SR-H is designed to burst at low pressures and operate in liquid or gas services and does not require special rupture disc holders. It fits between standard ASME BPE ferrules and other sanitary ferrules as noted below.

### TYPICAL APPLICATIONS

- Food Processing
- Beverage Processing
- Pharmaceutical Processing / Manufacturing
- Bio-Tech
- Many Clean-In-Place/Steam-In-Place (CIP/SIP) applications



SR-H Rupture Disc

### FEATURES AND BENEFITS

- Supplied with FDA approved gasket materials
- Non-fragmenting keeping metal fragments from contaminating media
- Rated for full vacuum without the aid of a vacuum support (see performance attributes)
- Constructed of 316/316L SST
- Standard sanitary packaging includes sanitary discs poly-bagged, nitrogen purged and sealed.
- 90% operating ratio
- Vertical tag to visually confirm proper installation
- Average surface finish of wetted surfaces:
  - Standard: 12-25 Ra
  - Electropolished: 8-16 Ra
- Burst Indicator solutions available

### OPTIONS

- Available with Teflon® liner (process side only)
- Electropolishing
- Integral Burst Indicator

Form No. R.1.01.01-7

## ACCESSORIES

SR-H rupture discs are designed for use in ASME BPE ferrules, DIN 32676 ferrules and NovAseptic® Connectors flush mount fittings. Other sizes and/or ferrule standards can be satisfied by using SR-H rupture discs in combination with appropriate transition ferrules.

In addition to the integral burst indicator option, the BCH Burst Indicator is designed for use with the SR-H disc utilizing ASME BPE ferrules and clamps. It provides instantaneous notification of rupture disc activation. Upon disc rupture, the BCH's thin Teflon® seal is bulged into a flexible circuit, causing the circuit to be physically broken. This open circuit condition can be used to activate alarms, bells, remote annunciators or interfaced with process control systems. For more information, see Fike Data Sheet R.1.02.01.

## MINIMUM/MAXIMUM BURST PRESSURES IN PSIG (BARG) @ 72°F (22°C)

316/316L SST			
In	Ferrule	Min. BP	Max. BP
1.5	ASME BPE	24 (1.65)	140 (9.65)
2	ASME BPE	20 (1.38)	100 (6.89)
3	ASME BPE	15 (1.03)	80 (5.51)
4	ASME BPE	12 (.83)	55 (3.79)
DN40	DIN 32676	24 (1.65)	140 (9.65)
DN50	DIN 32676	24 (1.65)	100 (6.89)

## AVAILABLE MANUFACTURING RANGES

Available Manufacturing Ranges	< 20 PSIG (1.38 BARG)	20 to 40 PSIG (1.38-2.76 BARG)	Greater than 40 PSIG (2.76 BARG)
+0/-10%	No	Yes	Yes
+0/-5%	No	No	Yes
+0/-2 PSIG	Yes	No	No
Zero	Yes	Yes	Yes

- Rupture discs stamped at 40 PSIG (2.76 BARG) and below shall use the following equation:  
Maximum Operating Pressure = (Marked Burst Pressure – 2 PSIG) x Operating Ratio
- Additional sizes and ferrule types available, consult factory.

## GASKET INFORMATION

Gasket Material	Minimum Service Temperature	Maximum Service Temperature
White EPDM*	-40°F (-40°C)	300°F (149°C)
Black EPDM	-40°F (-40°C)	300°F (149°C)
PTFE (Teflon)	-20°F (-28°C)	450°F (232°C)
Silicone	-40°F (-40°C)	450°F (232°C)
Viton	-20°F (-28°C)	450°F (232°C)
J-1500 (Filled PTFE)	-40°F (-40°C)	450°F (232°C)








\* 3-A approval applies to all gaskets except white EPDM. All gaskets are USP Class VI approved.

### Notes:

PTFE Teflon is subject to cold flow in gasketed connections and may result in leakage and/or the need for frequent re-tightening. J1500 is a filled PTFE composite that is highly resistant to cold flow and is a preferable alternative to PTFE in most applications.

## HOW TO SPECIFY

Previous Lot Number:			
OR			
Size:			
Burst Pressure:	@	(Temperature)	
Manufacturing Range:	Std:	Other:	
Liner:			
Gasket Material:			
Electropolished:	Yes / No		
Integral BI:			
Certifications:	ASME	CE	

Performance Attributes				Process Media		Rupture Disc Holders
Operating Ratio	Non-Fragmenting	Vacuum Resistant	Sanitary	Liquid	Vapor / Gas	Ferrules
						
90%	yes	yes*	yes	yes	yes	yes

\* For Burst Pressures less than 15 PSIG (1.03 BARG) consult factory.

## CERTIFICATIONS



SR-H "Contour Modified" design is covered by United States patents 5,467,886 and 5,267,666 and foreign Patents. Contour Modified and SR-H are trademarks of Fike Corporation. NovAseptic is a registered trademark of Millipore Inc.

*(This page is left blank intentionally)*



Copyright © Fike Corporation All Rights Reserved.  
Form No. R.1.01.01-7 May, 2009 Specifications are subject to change without notice.

---