

SRL RUPTURE DISC

DESCRIPTION

The Fike SRL rupture disc is reverse-bulged and perimeter-scored to facilitate opening without knife-blades. It is ideal for such demanding applications as the isolation of pressure relief valves. Sophisticated finite element analysis (FEA) techniques were used to develop the SRL's Contour Modified™ design.



SRL Rupture Disc

FEATURES AND BENEFITS

- SRL rupture discs can be used in a wide variety of applications including liquid, vapor and two phase media flow.
- SRL can operate up to 90% of its marked burst pressure for burst pressures over 40 PSIG (2.76 BARG), and up to 90% of the minimum of the burst tolerance at 40 PSIG (2.76 BARG) and below.
- SRL will withstand full vacuum without the aid of a vacuum support (see performance attributes).
- If damaged during normal installation, the rupture disc will open at less than 1.5 times the stamped burst pressure.
- SRL discs perform reliably even under less-than-ideal bolt loading conditions due to their special seating configuration.
- The perimeter score configuration, along with the integral ring, control its opening and enable the disc to rupture without fragmentation.
- The single hinge design helps achieve low burst pressure and full opening upon rupture.
- The DiscLoc™ locator tab prevents incorrect, inverted installation in the holder. Prominent flow arrows indicate the process flow direction during venting.

PRESSURE RELIEF VALVE APPLICATION

When SRL discs are used to isolate pressure relief valves, a combination capacity factor of 0.9 may be used. Higher combination capacity factors may be established by testing and certifying in accordance with ASME Code, Section VIII, Division 1. See Fike Technical Bulletin TB8103 for more information.

OPTIONS

- Available with fluoropolymer liner with a maximum temperature of 450°F (232°C)
- Polyurethane 250°F (121°C) and Teflon 450°F (232°C) protective coatings also available
- Standard O-rings are available in Viton with a maximum operating temperature of 450°F (232°C)

Form No. R.1.26.01-3

ACCESSORIES AND HOLDERS

XL Rupture Disc Holders*

XL holders achieve a bubbletight metal-to-metal seal with the disc, while maintaining tight rupture tolerances. To reduce fugitive emissions, an optional O-ring groove may be specified to accommodate an O-ring seal against the disc. The XL holder may also be ordered in pretorqueable style, allowing the correct torque to be achieved prior to field installation. For more information on XL holders, see the Insert and Pretorqueable Series XL Holder Data Sheet R1.05.01.

*Note: 1.5” requires SRL holder - not suitable for use in the 1.5” XL holder.

The Fike XL holder may be ordered with either 1/4” or 1/2” gauge tap for installation of pressure gauge, excess flow valve or other devices as specified by ASME Code, Section VIII, Div. 1 when used in combination with a pressure relief valve.

MINIMUM/MAXIMUM BURST PRESSURES IN PSIG (BARG) @ 72°F (22°C)

		316/316L SST		Inconel® 600		Monel® 400		Nickel 200/201		Hastelloy® C276		Tantalum	
		Max Temp: 900°F (482°C)		Max Temp: 1100°F (593°C)		Max Temp: 900°F (482°C)		Max Temp: 800°F (427°C)		Max Temp: 900°F (482°C)		Max Temp: 500°F (260°C)	
In	DN	Min. BP	Max. BP	Min. BP	Max. BP	Min. BP	Max. BP	Min. BP	Max. BP	Min. BP	Max. BP	Min. BP	Max. BP
1	25	50 (3.45)	275 (18.97)	50 (3.45)	155 (10.69)	30 (2.07)	185 (12.76)	30 (2.07)	85 (5.86)	60 (4.14)	320 (22.07)	30 (2.07)	185 (12.76)
1.5	40	50 (3.45)	275 (18.97)	50 (3.45)	155 (10.69)	30 (2.07)	185 (12.76)	30 (2.07)	85 (5.86)	60 (4.14)	320 (22.07)	30 (2.07)	185 (12.76)
2	50	25 (1.72)	230 (15.86)	25 (1.72)	180 (12.41)	18 (1.24)	160 (11.03)	18 (1.24)	75 (5.17)	45 (3.10)	265 (18.28)	25 (1.72)	150 (10.34)
3	80	22 (1.52)	190 (13.10)	22 (1.52)	150 (10.34)	15 (1.03)	140 (9.66)	15 (1.03)	60 (4.14)	40 (2.76)	200 (13.79)	15 (1.03)	140 (9.65)
4	100	20 (1.38)	180 (12.41)	20 (1.38)	150 (10.34)	12 (.83)	140 (9.66)	12 (.83)	50 (3.45)	35 (2.41)	160 (11.03)	12 (.83)	115 (7.93)
6	150	18 (1.24)	150 (10.34)	18 (1.24)	150 (10.34)	10 (.69)	125 (8.62)	10 (.69)	50 (3.45)	32 (2.21)	115 (7.93)	10 (.69)	100 (6.90)
8	200	17 (1.17)	135 (9.35)	17 (1.17)	130 (8.97)	10 (.69)	110 (7.59)	10 (.69)	70 (4.83)	30 (2.07)	115 (7.93)	10 (.69)	80 (5.52)

AVAILABLE MANUFACTURING RANGES

Available Manufacturing Ranges	< 20 PSIG (1.38 BARG)	Between 20 to 40 PSIG (1.38-2.76 BARG)	Greater than 40 PSIG (2.76 BARG)
+0/-10%	No	Standard	Standard
+0/-5%	No	No	Yes
+0 PSIG to -2 PSIG (.14 BARG)	Standard	No	No
Zero	Yes	Yes	Yes

BURST/PERFORMANCE TOLERANCE

Marked Burst Pressure		Tolerance	
PSIG	BARG	PSIG	BARG
≤ 40	≤ 2.76	± 2	± .14
> 40	> 2.76	± 5%	± 5%


HOW TO SPECIFY

Previous Lot Number:		
OR		
Size:		
Flange Rating:		
Burst Pressure:	@	(Temperature)
Seal Material:		
Ring Material:		
Manufacturing Range:	Std:	Other:
Coatings:		
Optional O-Rings:	Yes / No	Qty:
Certification:	ASME	CE

Performance Attributes			Process Media		Rupture Disc Holders	
Operating Ratio	Non-Fragmenting	Vacuum Resistant	Liquid	Vapor/Gas	Bolted/Type	Pre-Torque
90%	yes	yes*	yes	yes	yes	yes

* Consult factory if full vacuum is required and specified burst pressure is below 15 PSIG (1.03 BARG)

CERTIFICATIONS



SRL design is covered by United States patents 5,467,886 and foreign patents. SRL is a trademark of Fike Corporation.



Copyright © Fike Corporation All Rights Reserved.
Form No. R.1.26.01-3 June, 2009 Specifications are subject to change without notice.